


LASTRE A FISSAGGIO NASCOSTO

GENUS 330



ACCIAIO

spessore (mm)	peso (Kg/m ²)	Jxx (cm ⁴ /m)	Wxx (cm ³ /m)
0,60	7,33	3,55	2,33
0,80	9,77	4,85	3,13
1,00	12,22	6,14	3,94



spessore	interasse cm						
SP	60	80	100	120	150	200	250
0,60	810	455	259	150	77	-	-
0,80	1090	613	354	205	105	-	-
1,00	1372	772	448	259	133	56	-




carico utile massimo Kg/m²
(compreso peso proprio)


spessore	interasse cm						
SP	60	80	100	120	150	200	250
0,60	1062	597	382	265	170	81	57
0,80	1429	804	514	357	229	111	78
1,00	1799	1012	648	450	288	140	98

ALLUMINIO

spessore (mm)	peso (Kg/m ²)	Jxx (cm ⁴ /m)	Wxx (cm ³ /m)
0,70	2,94	4,14	2,68
0,80	3,36	4,79	3,09
1,00	4,20	6,14	3,94




spessore	interasse cm						
SP	60	80	100	120	150	200	250
0,70	229	129	83	57	-	-	-
0,80	265	149	95	66	-	-	-
1,00	337	190	121	84	-	-	-




carico utile massimo Kg/m²
(compreso peso proprio)

spessore	interasse cm						
SP	60	80	100	120	150	200	250
0,70	301	169	108	75	-	-	-
0,80	347	195	125	87	56	-	-
1,00	442	249	159	111	71	-	-

GENUS 460



spessore (mm)	peso (Kg/m ²)	Jxx (cm ⁴ /m)	Wxx (cm ³ /m)
0,60	6,59	2,55	1,67
0,80	8,79	3,48	2,25
1,00	10,99	4,41	2,83




spessore	interasse cm						
SP	60	80	100	120	150	200	250
0,60	581	327	186	108	55	-	-
0,80	782	440	254	147	75	-	-
1,00	984	554	322	186	95	-	-




carico utile massimo Kg/m²
(compreso peso proprio)

spessore	interasse cm						
SP	60	80	100	120	150	200	250
0,60	762	428	274	190	122	58	-
0,80	1025	577	369	256	164	79	56
1,00	1291	726	465	323	207	100	71



spessore	interasse cm						
SP	60	80	100	120	150	200	250
0,70	165	93	59	-	-	-	-
0,80	190	107	69	-	-	-	-
1,00	242	136	87	61	-	-	-



carico utile massimo Kg/m²
(compreso peso proprio)

spessore	interasse cm						
SP	60	80	100	120	150	200	250
0,70	216	121	78	54	-	-	-
0,80	249	140	90	62	-	-	-
1,00	317	178	114	79	51	-	-

